

B17 The invention relates to a lining for columns of automobiles, comprising a base area with fixing and holding elements and at least one opening area, covering an airbag, for example.

In many automobiles of more recent design, it is common, in addition to the airbags which are arranged in the steering wheel cover or in the dashboard on the passenger's side, also to provide side airbags, as they are called, as a supplement, which may be integrated into the side lining of the automobile. For example, side airbags of this type are accommodated in the column lining of the automobiles.

In this connection, EP 0 894 679 A has disclosed a column lining for columns of automobiles which comprises at least one opening area and at least one fixing area.

In this case, the fixing area consists of a relatively hard thermoplastic from the group comprising polypropylene, acryl butadiene styrene copolymers and acryl butadiene styrene polycarbonate copolymers with a Shore A hardness greater than 100. On the other hand, the entire opening area consists of a softer thermoplastic with a preferred Shore A hardness of from 60 to 80. By using two thermoplastics of differing hardness, splintering of the column lining when the airbag is triggered or emerges is largely avoided.

One drawback is simply that the column linings in automobiles in particular are exposed to high temperature loadings or great temperature fluctuations, and the opening area consisting of a relatively soft thermoplastic material cannot meet the strict requirements with regard to dimensional stability.

It is an object of the invention to improve a column lining of the type mentioned at the beginning in such a way that adequate dimensional stability is ensured with simple means.

According to the invention, this object is achieved by the opening area consisting largely of a thermoplastic material with a Shore A hardness greater than 100 and having a hinge area, adjoining the base area, consisting of a thermoplastic material with a Shore A hardness of less than 95.

According to the invention, a large part of the opening area can thus consist of the same thermoplastic material as the base area and can be produced with the latter in one operation. Only a hinge area of the opening area, integrated into the base area, consists of a softer thermoplastic material with a Shore A hardness of less than 90. Since the majority of the opening area consists of the harder material, adequate dimensional stability of the lining part can be achieved.

If the hinge area does not reach as far as the edge of the respective lining part, according to the invention the

17121
 17122
 17123
 17124
 17125
 17126
 17127
 17128
 17129
 17130
 17131
 17132
 17133
 17134
 17135
 17136
 17137
 17138
 17139
 17140
 17141
 17142
 17143
 17144
 17145
 17146
 17147
 17148
 17149
 17150
 17151
 17152
 17153
 17154
 17155
 17156
 17157
 17158
 17159
 17160
 17161
 17162
 17163
 17164
 17165
 17166
 17167
 17168
 17169
 17170
 17171
 17172
 17173
 17174
 17175
 17176
 17177
 17178
 17179
 17180
 17181
 17182
 17183
 17184
 17185
 17186
 17187
 17188
 17189
 17190
 17191
 17192
 17193
 17194
 17195
 17196
 17197
 17198
 17199
 17200
 17201
 17202
 17203
 17204
 17205
 17206
 17207
 17208
 17209
 17210
 17211
 17212
 17213
 17214
 17215
 17216
 17217
 17218
 17219
 17220
 17221
 17222
 17223
 17224
 17225
 17226
 17227
 17228
 17229
 17230
 17231
 17232
 17233
 17234
 17235
 17236
 17237
 17238
 17239
 17240
 17241
 17242
 17243
 17244
 17245
 17246
 17247
 17248
 17249
 17250
 17251
 17252
 17253
 17254
 17255
 17256
 17257
 17258
 17259
 17260
 17261
 17262
 17263
 17264
 17265
 17266
 17267
 17268
 17269
 17270
 17271
 17272
 17273
 17274
 17275
 17276
 17277
 17278
 17279
 17280
 17281
 17282
 17283
 17284
 17285
 17286
 17287
 17288
 17289
 17290
 17291
 17292
 17293
 17294
 17295
 17296
 17297
 17298
 17299
 17300
 17301
 17302
 17303
 17304
 17305
 17306
 17307
 17308
 17309
 17310
 17311
 17312
 17313
 17314
 17315
 17316
 17317
 17318
 17319
 17320
 17321
 17322
 17323
 17324
 17325
 17326
 17327
 17328
 17329
 17330
 17331
 17332
 17333
 17334
 17335
 17336
 17337
 17338
 17339
 17340
 17341
 17342
 17343
 17344
 17345
 17346
 17347
 17348
 17349
 17350
 17351
 17352
 17353
 17354
 17355
 17356
 17357
 17358
 17359
 17360
 17361
 17362
 17363
 17364
 17365
 17366
 17367
 17368
 17369
 17370
 17371
 17372
 17373
 17374
 17375
 17376
 17377
 17378
 17379
 17380
 17381
 17382
 17383
 17384
 17385
 17386
 17387
 17388
 17389
 17390
 17391
 17392
 17393
 17394
 17395
 17396
 17397
 17398
 17399
 17400
 17401
 17402
 17403
 17404
 17405
 17406
 17407
 17408
 17409
 17410
 17411
 17412
 17413
 17414
 17415
 17416
 17417
 17418
 17419
 17420
 17421
 17422
 17423
 17424
 17425
 17426
 17427
 17428
 17429
 17430
 17431
 17432
 17433
 17434
 17435
 17436
 17437
 17438
 17439
 17440
 17441
 17442
 17443
 17444
 17445
 17446
 17447
 17448
 17449
 17450
 17451
 17452
 17453
 17454
 17455
 17456
 17457
 17458
 17459
 17460
 17461
 17462
 17463
 17464
 17465
 17466
 17467
 17468
 17469
 17470
 17471
 17472
 17473
 17474
 17475
 17476
 17477
 17478
 17479
 17480
 17481
 17482
 17483
 17484
 17485
 17486
 17487
 17488
 17489
 17490
 17491
 17492
 17493
 17494
 17495
 17496
 17497
 17498
 17499
 17500
 17501
 17502
 17503
 17504
 17505
 17506
 17507
 17508
 17509
 17510
 17511
 17512
 17513
 17514
 17515
 17516
 17517
 17518
 17519
 17520
 17521
 17522
 17523
 17524
 17525
 17526
 17527
 17528
 17529
 1

opening area can be bounded by intended fracture lines, wall thickness reductions, etc. adjoining the hinge area.

A visually satisfactory appearance is ensured by the base area and the opening area, together with the hinge area, being covered by a unified decorative layer.

The invention will be explained in more detail below by using drawings. Figure 1 shows a lining according to the invention for columns of automobiles in plan view, and figure 2 shows a section along the line II-II in figure 1 in an enlarged illustration.

The column lining illustrated in figures 1 and 2 has a base area 1 and an opening area 2, the opening area 2 covering an airbag 3, for example. As can be seen from figure 2, the base area 1 has fixing and holding elements 4, with which the lining part can be fixed to the column 5 of the automobile. The opening area 2 largely consists of a thermoplastic material with a Shore A hardness greater than 100, only a hinge area 6 adjoining the base area 1 consists of a softer thermoplastic material with a Shore A hardness of less than 90.

The hinge area 6 may reach as far as the outer edge of the lining part or, as illustrated in figure 1, can have intended fracture lines or wall thickness reductions 7 adjoining the hinge area 6.

The hinge area advantageously consists of a thermoplastic material with a Shore A hardness between 30 and 95, preferably with a Shore A hardness between 60 and 80.

200001454650

Suitable materials for the hinge area 6 are, in particular, thermoplastic elastomers or elastomer alloys of thermoplastics and elastomers.

The base area 1 and the opening area 2, together with the hinge area 6, can preferably be covered by a unified decorative layer.

[illegible]